

Section Mills

Section mills are essential tools for milling casing sections in instances such as sidetracking and gravel packing, as well as for perforating zones. AEI's supplied section mill is available in various casing sizes, ranging from 4-1/2" to 13-3/8". All blades are sharpened, allowing for the simultaneous milling of the casing. The milling rate is dependent on the fluid's capability of removing cuttings during the process.

Model	Connection	Body O.D (mm)	Max. OD when cutter opened (mm)	OD of stabilizer block		Casing Size (in)
				Casing wallthickness (mm)	OD of stabilizer block (mm)	
DX114	2 3/8 REG	96	130	5.2	100	4 1/2
				5.68	99	
				6.35	98	
				5.59	112	
DX127	2 7/8 REG	104	150	6.43	111	5
				7.52	108	
				6.2	124	
DX140	2 7/8 REG	114	165	6.98	122	5 1/2
				7.72	121	
				7.32	150	
DX168	3 1/2 REG	140	200	8.94	147	6 5/8
				10.59	144	
				12.06	141	
				8.03	158	
DX178	3 1/2 REG	152	215	9.19	156	7
				10.36	154	
				7.92	225	
				8.94	223	
DX245	4 1/2 REG	210	310	10.03	221	9 5/8
				11.05	218	
				11.99	216	
				8.38	319	
DX340	6 5/8 REG	292	394	9.65	316	13 3/8
				10.92	314	
				12.19	311	
				13.06	309	



+971 52 864 9998



www.aeisupplies.com
info@aeisupplies.com



United Arab Emirates | Pakistan | United States of America